

Filtri a tamburo



ITF - 30



ITF - 50



ITF - 80



ITF - 120



ITF - 240



modello

itf- 30

itf- 50

itf- 80

itf- 120

itf- 240

Lago per koi	30 m ³	50 m ³	80 m ³	120 m ³	240 m ³
Lago balneabile	50 m ³	80 m ³	120 m ³	200 m ³	400 m ³
Portata massima/ora	25 m ³	35 m ³	50 m ³	65 m ³	140 m ³
Portata consigliata/ora	20 m ³	30 m ³	45 m ³	60 m ³	120 m ³
Bio-camera integrata	-	-	-	-	-
Pompa per controlavaggio	✓	✓	✓	✓	✓
Pompa contr. integrata/esterna	esterna	esterna	integrata	integrata	integrata
Controllo 'Clever' incluso	✓	✓	✓	✓	✓
Controllo 'Comfort'	opzionale	opzionale	opzionale	opzionale	opzionale
Larghezza maglia Inox 304	70 µ	70 µ	70 µ	70 µ	70 µ
Insonorizzazione	✓	✓	✓	✓	✓
Alimentazione gravità/pompa	✓/✓	✓/✓	✓/✓	✓/✓	✓/✓
Predisposizione UVC	✓	✓	✓	✓	✓
UVC consigliato	UV-C 60	UV-C 60 / 80	UV-C 80	UV-C 120	2x UV-C 120
Ingresso	2 x 110 mm	3 x 110 mm	4 x 110 mm	5 x 110 mm	1 x 300 mm
Uscita	1 x 160 mm	1 x 160 mm	4 x 110 mm	5 x 110 mm	1 x 300 mm
Scarico acqua	1 x 110 mm	1 x 110 mm	1 x 110 mm	1 x 110 mm	1 x 110 mm
Dimensioni (L/L/H) in mm	730/630/600	730/730/600	1100/730/700	1250/730/700	1040/1090/985
Materiale Inox 304	✓	✓	✓	✓	✓
Garanzia*	2 anni	2 anni	2 anni	2 anni	2 anni

* Ad eccezione della copertura tamburo

Ulteriore sviluppo e modifiche tecniche riservati.